

TurnPro™

HYDRAULIC SWAGING TOOL

The TurnPro Hydraulic Swaging Tool swages 3/4" inch and larger SSP Duolok tube fitting ferrules onto the tubing prior to assembly to the fitting body. Using hydraulic pressure, the SSP Hydraulic Swaging Tool overcomes the challenge of manually applying the torque required to install 3/4" inch and larger tube fittings. The SSP Hydraulic Swaging Tool reduces installation time and assures sufficient make-up for leak-tight connections on larger Duolok tube fitting sizes.



Part Number	Description
TP-HST	Swage Tool Assembly
TP-HST-P32	Swage Tool Piston 2"
TP-HST-A2024	Swage Tool Adapter 1-1/4" - 1-1/2"
TP-HST-P24	Swage Tool Piston 1-1/2"
TP-HST-P20	Swage Tool Piston 1-1/4"
TP-HST-A16	Swage Tool Adapter 1"
TP-HST-P16	Swage Tool Piston 1"

KEY BENEFITS

- ▶ Places no initial strain on nut, fitting body threads or fitting body sealing surfaces.
- ▶ Preswages SSP Duolok tube fitting ferrules onto tubing.
- ▶ Installed fittings are 100% gaugeable.

KEY FEATURES

- ▶ Quick and easy tooling changes to install 3/4", 1", 1-1/4", 1-1/2" and 2" Duolok tube fittings.
- ▶ Instructions printed on tool base.
- ▶ View window for verification of complete swage.
- ▶ Rugged plastic, wheeled case with pull handle.
- ▶ Minimal setup time.

SSP • 8250 BOYLE PARKWAY • TWINSBURG, OH 44087 • +1.330.425.4250

mySSPusa.com/TurnPro

